

ALDI STORES

ALDI STORE DALYELLUP

ENVIRONMENTAL ACOUSTIC ASSESSMENT

NOVEMBER 2024

OUR REFERENCE: 33171-3-24288



DOCUMENT CONTROL PAGE

ENVIRONMENTAL ACOUSTIC ASSESSMENT

ALDI STORE – DALYELLUP

Job No: 24288

Document Reference: 33171-3-24288

FOR

ALDI STORES

		DOCUMENT INFO	ORMATION			
Author:	George Watts		Checked By:		Paul Daly	
Date of Issue :	14 August 2024	ı.				
		REVISION HI	STORY			
Revision	Description		Dat	e	Author	Checked
1	Revision for ne	w DA drawings set	6/1	1/2024	GW	
2	Revision for new DA drawings set		7/1	7/11/2024 GW		
Copy No.	Version No.	DOCUMENT DIS	TRIBUTION	Hard (Conv	Electronic Copy
copy ito.	version ivo.	Aldi Stores		ilaia (СОРУ	Liectronic copy
1	3	Attn : Nicholas Zubrowski				✓
		Email : Nicholas.zubrowski	@aldi.com.au			

CONTENTS

1.	INTRODUCTION	1
2.	SUMMARY	1
3.	CRITERIA 3.1 Environmental Protection (Noise) Regulations 1997	1 1
4.	PROPOSED DELIVERIES	4
5.	MECHANICAL PLANT	4
6.	METHODOLOGY	4
7.	RESULTS	6

<u>APPENDICES</u>

A DEVELOPMENT PLANS

Herring Storer Acoustics Our ref: 33171-3-24288 1

1. INTRODUCTION

Herring Storer Acoustics were commissioned by Aldi Stores to undertake an acoustic assessment of noise emissions associated with the proposed Aldi Store to be located in Dalyellup, on the corner of Portobello Road and Grafton Lane.

The objective of this study was to assess noise emissions from delivery vehicles and mechanical services at the noise sensitive premises surrounding the proposed site for compliance with the requirements of the *Environmental Protection (Noise) Regulations 1997*.

The assessment was undertaken to inform the design development team of the store and address likely development approval conditions.

The site plan is attached in Appendix A.

2. SUMMARY

Noise emissions associated with the proposed Aldi store have been determined to comply with the Environmental Protection (Noise) Regulations at all noise sensitive premises in the area.

It is noted that our assessment has assumed that refrigeration equipment and engines are turned off during unloading within the loading dock. It is noted that this is a recommendation, however compliance would still be achieved with the trucks operating refrigeration equipment within the dock. A 2.5m loading dock wall has been included in our noise modelling calculations.

Mechanical plant noise emissions have been calculated to achieve compliance with the applicable Assigned Noise Levels at all times for all noise sensitive premises considered. Mechanical plant has been assumed to be located on the roof of the proposed Aldi store in the vicinity of the loading dock. No barriering of the mechanical plant has been included in our modelling/assessment.

3. <u>CRITERIA</u>

3.1 <u>ENVIRONMENTAL PROTECTION (NOISE) REGULATIONS 1997</u>

The *Environmental Protection (Noise) Regulations 1997* stipulate the allowable noise levels at any noise sensitive premises from other premises. The allowable noise level is determined by the calculation of an influencing factor, which is added to the baseline criteria set out in Table 1 of the Regulations. The baseline assigned noise levels are listed in Table 3.1.

TABLE 3.1 – ASSIGNED NOISE LEVELS

Premises Receiving	Time of Day	Assigned Level (dB)			
Noise	Time of Day	L _{A 10}	L _{A 1}	L _{A max}	
Noise sensitive premises within 15 metres of a dwelling (Highly Sensitive Areas)	0700 - 1900 hours Monday to Saturday	45 + IF	55 + IF	65 + IF	
	0900 - 1900 hours Sunday and Public Holidays	40 + IF	50 + IF	65 + IF	
	1900 - 2200 hours all days	40 + IF	50 + IF	55 + IF	
	2200 hours on any day to 0700 hours Monday to Saturday and 0900 hours Sunday and Public Holidays	35 + IF	45 + IF	55 + IF	

Note: The L_{A10} noise level is the noise that is exceeded for 10% of the time.

The L_{A1} noise level is the noise that is exceeded for 1% of the time.

The L_{Amax} noise level is the maximum noise level recorded.

It is a requirement that noise from the site be free of annoying characteristics (tonality, modulation and impulsiveness) at other premises, defined below as per Regulation 9.

"impulsiveness"

means a variation in the emission of a noise where the difference between L_{Apeak} and $L_{Amax\,Slow}$ is more than 15dB when determined for a single representative event;

"modulation"

means a variation in the emission of noise that -

- (a) is more than 3dB $L_{A\ Fast}$ or is more than 3dB $L_{A\ Fast}$ in any one-third octave band;
- (b) is present for more at least 10% of the representative assessment period; and
- (c) is regular, cyclic and audible;

"tonality"

means the presence in the noise emission of tonal characteristics where the difference between –

- (a) the A-weighted sound pressure level in any one-third octave band; and
- (b) the arithmetic average of the A-weighted sound pressure levels in the 2 adjacent one-third octave bands,

is greater than 3 dB when the sound pressure levels are determined as $L_{Aeq,T}$ levels where the time period T is greater than 10% of the representative assessment period, or greater than 8 dB at any time when the sound pressure levels are determined as $L_{A\,Slow}$ levels.

Where the above characteristics are present and cannot be practicably removed, the following adjustments are made to the measured or predicted level at other premises.

TABLE 3.2 – ADJUSTMENTS FOR ANNOYING CHARACTERISTICS

Where tonality is present	Where modulation is present	Where impulsiveness is present
+ 5 dB	+ 5 dB	+ 10 dB

The following locations have been determined to require an assessment of noise level emissions.

The receiver locations considered are shown below in Figure 3.1.




FIGURE 3.1 – RECEIVER POINTS

The influencing factor at the neighbouring residential premises (both proposed and existing) has been calculated based on the following:

Secondary Roads within the Inner circle;

Norton Promenade + 2 dB Parade Road + 2 dB

Commercial Premises within the inner circle;

40 % + 2 dB

Commercial Premises within the outer circle;

20 % + 1 dB

Hence, the influencing factor is estimated at 7 dB.

Based on the above influencing factor, the assigned outdoor noise levels are listed in Table 3.3.

TABLE 3.3 - ASSIGNED OUTDOOR NOISE LEVEL

Premises	Time of Day		Assigned Level (dB)		
Receiving Noise			L _{A 1}	L _{A max}	
	0700 - 1900 hours Monday to Saturday (Day)		62	72	
Noise sensitive	0900 - 1900 hours Sunday and Public Holidays (Sundays)		57	72	
premises	1900 - 2200 hours all days (Evening)	47	57	62	
premises	2200 hours on any day to 0700 hours Monday to Saturday and 0900 hours Sunday and Public Holidays (Night)	42	52	62	

Note:

L_{A10} is the noise level exceeded for 10% of the time.

 L_{A1} is the noise level exceeded for 1% of the time.

 $L_{\mbox{\scriptsize Amax}}$ is the maximum noise level.

4. PROPOSED DELIVERIES

The use of the delivery dock is understood to accommodate 19m articulated delivery trucks and have been assumed to be refrigerated trucks (i.e worst case scenario). In addition to the larger deliveries a bakery delivery occurring between 5am and 7am each morning has been assumed to be a 13m rigid truck.

The truck types assumed in our assessment have been determined through consultation with ALDI stores.

It is noted that we have assumed that the carpark leading to the delivery dock is a public place, hence we have only considered delivery truck noise levels as they enter the dock itself— outside of this space the trucks are in a public area and therefore compliance with the Regulations are not applicable and hence have not been considered.

5. <u>MECHANICAL PLANT</u>

Mechanical plant details have been based on information provided for previous Aldi stores and provided information are located on the ground level to the south of the building.

A barrier at least 1m above the height of the top of the equipment has been assumed to be in place around the equipment, based on preliminary calculations indicating that this is required.

The barrier is required to be of surface density not less than 14kg/m².

The barrier is to be constructed of 9mm thick compressed fibre cement sheeting, with no gaps, to the internal face of the plant area with solid colorbond cladding to the external face.

Acoustic data is contained in Table 6.3.

6. <u>METHODOLOGY</u>

Noise modelling of the noise propagation from the site was carried out using the environmental noise modelling computer program, "SoundPlan". Single point calculations were undertaken.

Input data for computer modelling included:

- Design of store as per drawings in Appendix A.
- EPA standard weather condition for the day and night periods (see Table 6.1).
- Sound power levels, as summarised in Table 6.2.

TABLE 6.1 - WEATHER CONDITIONS

Condition	Day Period	Night Period		
Temperature	20 °C	15 °C		
Relative humidity	50%	50%		
Pasquil Stability Class	E	F		
Wind speed	4 m/s*	3 m/s*		

^{*} From source to receiver

TABLE 6.2 – SOUND POWER LEVELS OF DELIVERY VEHICLES

DESCRIPTION	dB(A)
19m articulated delivery truck with refrigeration unit	97
13m rigid delivery truck	85

TABLE 6.3 – NOISE LEVELS OF MECHANICAL PLANT

DESCRIPTION	dB(A)	
Condenser Unit (Daikin RXYQ54TNY1A(E))	67 dB(A) @ 3m	
Refrigeration Plant	61 dB(A) @ 3m	
R134A Aldi Pack	61.8 dB(A) @ 3m	

For the above sound power levels, single point calculations were undertaken for the following scenarios :

Scenario 1: One large refrigerated truck delivery.

Scenario 2: One 13m rigid truck delivery (bakery delivery).

Scenario 3: Mechanical Plant.

Note: For the noise to be less than 10% of the time and be assessed under the $L_{\rm A1}$ assigned noise levels, the truck engines and refrigeration units would need to be turned off while unloading is occurring

The L_{A1} assigned noise level would be the pertinent prescribed noise level in this instance (for deliveries) as the duration of time that the noise of the deliveries is present is less than 10% of a representative time period. The noise associated with the delivery is the manoeuvring of the truck into place, upon which the truck is switched off – hence – even if the delivery takes some time (i.e. 30-60 minutes) the noise level associated with the truck is not present throughout the duration of the delivery.

It is noted that this also means the noise assessment is more "realistic" as if the L_{A10} parameter was to be used as the noise level associated with the truck is not present for more than 10% of a representative time period, the L_{A10} noise level would be at the ambient noise level of the area, rather than the truck noise.

A height of 2.5m has been assumed for the delivery dock wall.

Mechanical plant has been assumed to be located on the roof of the proposed store, in the vicinity of the loading dock. No barriering has been included in our modelling/assessment.

7. RESULTS

Single point calculations were undertaken for all locations shown in Figure 3.1, with the results of the modelling listed in Table 7.1.

TABLE 7.1 – RESULTANT NOISE LEVEL

Receiver Location	Scenario / Calculated Noise Level, (dB(A))				
Receiver Location	Scenario 1	Scenario 2	Scenario 3		
R1	26	15	37		
R2	27	16	37		
R3	28	17	37		
R4	30	17	36		
R5	29	16	36		
R6	28	16	36		
R7	28	16	36		
R8	27	15	36		
R9	26	14	35		
R10	25	13	35		

Based on the definitions of tonality, noise emissions from truck movements, being an L_{A1} , being present for less than 10% of the time, would not be considered tonal.

Noise levels associated with mechanical services activity could contain tonal characteristics, hence, a + 5 dB adjustment would be applicable.

Therefore, the assessable noise levels for each of the noise sources are listed below in Table 7.2.

TABLE 7.2 – ASSESSABLE NOISE LEVELS

TABLE 7.2 – ASSESSABLE NOISE LEVELS				
Dessiver Leastion	Scenario / Assessable Noise Level, (dB(A))			
Receiver Location	Scenario 1	Scenario 2	Scenario 3	
R1	26	15	42	
R2	27	16	42	
R3	28	17	42	
R4	30	17	41	
R5	29	16	41	
R6	28	16	41	
R7	28	16	41	
R8	27	15	41	
R9	26	14	40	
R10	25	13	40	

Tables 7.3 and 7.4 compares the assessable noise level for large truck deliveries and small truck deliveries against the relevant L_{A1} Assigned Noise Levels for the day, evening (and Sundays) and night periods. Noise levels that are calculated to exceed the relevant criteria are listed in red.

TABLE 7.3 – ASSESMENT OF NOISE LEVEL – SCENARIO 1 LARGE TRUCK DELIVERIES

Receiver	Assessable Noise Level, dB(A)	Accident Maica Laval L., dR		
Location	Scenario 1	Time of Day	L _{A1} dB	Assigned Noise Level
		Day	62	Complies
	26	Sundays	57	Complies
R1	26	Evening	57	Complies
		Night	52	Complies
		Day	62	Complies
D2	27	Sundays	57	Complies
R2	27	Evening	57	Complies
		Night	52	Complies
		Day	62	Complies
D2	20	Sundays	57	Complies
R3	28	Evening	57	Complies
		Night	52	Complies
		Day	62	Complies
D.4	20	Sundays	57	Complies
R4	30	Evening	57	Complies
		Night	52	Complies
		Day	62	Complies
DE	20	Sundays	57	Complies
R5	29	Evening	57	Complies
		Night	52	Complies
		Day	62	Complies
D.C.	20	Sundays	57	Complies
R6	28	Evening	57	Complies
		Night	52	Complies
		Day	62	Complies
D.7	20	Sundays	57	Complies
R7	28	Evening	57	Complies
		Night	52	Complies
		Day	62	Complies
D0	27	Sundays	57	Complies
R8	27	Evening	57	Complies
		Night	52	Complies
		Day	62	Complies
DO.	26	Sundays	57	Complies
R9	26	Evening	57	Complies
		Night	52	Complies
		Day	62	Complies
D40	25	Sundays	57	Complies
R10	25	Evening	57	Complies
		Night	52	Complies

TABLE 7.4 – ASSESMENT OF NOISE LEVEL – SCENARIO 2 SMALL TRUCK DELIVERIES

Receiver	Assessable Noise Level, dB(A)	Assigned Noise Level L., dR		
Location	Scenario 2	Time of Day	L _{A1} dB	Assigned Noise Leve
D4		Day	62	Complies
	15	Sundays	57	Complies
R1	15	Evening	57	Complies
		Night	52	Complies
		Day	62	Complies
D2	10	Sundays	57	Complies
R2	16	Evening	57	Complies
		Night	52	Complies
		Day	62	Complies
D2	17	Sundays	57	Complies
R3	17	Evening	57	Complies
		Night	52	Complies
		Day	62	Complies
5.4	4-	Sundays	57	Complies
R4	17	Evening	57	Complies
		Night	52	Complies
		Day	62	Complies
5.5	16	Sundays	57	Complies
R5	16	Evening	57	Complies
		Night	52	Complies
		Day	62	Complies
		Sundays	57	Complies
R6	16	Evening	57	Complies
		Night	52	Complies
		Day	62	Complies
	16	Sundays	57	Complies
R7	16	Evening	57	Complies
		Night	52	Complies
		Day	62	Complies
D.C.	45	Sundays	57	Complies
R8	15	Evening	57	Complies
		Night	52	Complies
		Day	62	Complies
DC	14	Sundays	57	Complies
R9	14	Evening	57	Complies
		Night	52	Complies
		Day	62	Complies
D4.0	10	Sundays	57	Complies
R10	13	Evening	57	Complies
		Night	52	Complies

Table 7.5 compares the assessable noise level for mechanical plant against the relevant L_{A10} Assigned Noise Levels for the day, evening (and Sundays) and night periods. Noise levels that are calculated to exceed the relevant criteria are listed in red.

Our ref: 33171-3-24288

TABLE 7.5 – ASSESMENT OF NOISE LEVEL – SCENARIO 3 – MECHANICAL PLANT


Receiver Location	Assessable Noise Receiver Location Assessable Noise Level, dB(A) Assigned Noise Level		Level, L _{A10} dB	Exceedance to
	Scenario 3	Time of Day	L _{A10} dB	Assigned Noise Level
		Day	52	Complies
R1	42	Sundays	47	Complies
KI	42	Evening	47	Complies
		Night	42	Complies
		Day	52	Complies
R2	42	Sundays	47	Complies
KZ	42	Evening	47	Complies
		Night	42	Complies
		Day	52	Complies
D 2		Sundays	47	Complies
R3	42	Evening	47	Complies
		Night	42	Complies
		Day	52	Complies
5.4		Sundays	47	Complies
R4	41	Evening	47	Complies
		Night	42	Complies
		Day	52	Complies
		Sundays	47	Complies
R5	41	Evening	47	Complies
		Night	42	Complies
		Day	52	Complies
D.C.		Sundays	47	Complies
R6	41	Evening	47	Complies
		Night	42	Complies
		Day	52	Complies
D.7		Sundays	47	Complies
R7	41	Evening	47	Complies
		Night	42	Complies
		Day	52	Complies
D.C.		Sundays	47	Complies
R8	41	Evening	47	Complies
		Night	42	Complies
		Day	52	Complies
D.C.		Sundays	47	Complies
R9	40	Evening	47	Complies
		Night	42	Complies
		Day	52	Complies
D4.0	1	Sundays	47	Complies
R10	40	Evening	47	Complies
		Night	42	Complies

Truck deliveries (both refrigerated and bakery delivery trucks) have been calculated to comply at all times.

Noise levels associated with the mechanical plant has also been calculated to comply at all times on the basis that the equipment is located on the roof of the store, in the vicinity of the loading dock. No barriering of mechanical plant has been included in our modelling/assessment.

APPENDIX A

DEVELOPMENT PLANS



NOTES

ORIGINAL A3

Copyright Nielsen Architects. Copyring, reproduction or use of this design or drawing in whole or part is prohibited without the written consent of Nielsen Architects. Use figured dimensions only - Do not scale. Check all dimensions on site prior to fabrication or setout.

DATE	DESCRIPTION	DRN	CHKD
05.11.24	REV PLANNING	LT	TB
07.11.24	REV PLANNING	LT	TB

PROPERTY DESCRIPTION	
TOTAL ALDI DEVELOPMENT ARFA	5465m²
PROPOSED ALDI BOUNDARY	
EXISTING BOUNDARIES	



CLIENT ALDI STORES


PROJECT ALDI DALYELLUP PORTOBELLO ROAD DALYELLUP W.A.

DRAWING LOCALITY PLAN



2.O. Box 691 Stirling SA 5152

SCALE	DATE	DRAWN	CHECKED
1:1500	NOV 2024	DS	TB
PROJECT No	DRAWING No	STATUS	REV
2976	DA00.01	DA	B








: 08 8339 8008 2.O. Box 691 Stirling SA 5152

SCALE	DATE	DRAWN	CHECKEI
1:1000	NOV 2024	DS	TB
PROJECT No	DRAWING No	STATUS	REV
2976	DA01.01	DA	-






2.O. Box 691 Stirling SA 5152 NIELSEN ARCHITECTS

ORIGINAL A3

DRN CHKD

SCALE	DATE	DRAWN	CHECKE
1:500	NOV 2024	DS	TB
PROJECT No	DRAWING No	STATUS	REV -



PROPOSED SITE & FLOOR PLAN

NOTES

ORIGINAL A3

Copyright Nielsen Architects. Copying, reproduction or use of this design or drawing in whole or part is prohibited without the written consent of Nielsen Architects. Use figured dimensions only - Do not scale. Check all dimensions on site prior to fabrication or setout.

REV	DATE	DESCRIPTION	DRN	CHK
Α	05.11.24	REV PLANNING	LT	TB
В	07.11.24	REV PLANNING	LT	TB

AREA m²
1505m²
1443m²
1033m²
67m²
1100m²
268m²
227m²
17m²
24m²
75m²
62m²
AREA m²
5465m²
3960m²
1840m²
1197m²
187m²
736m²
85
1505m²



ALDI STORES




DRAWING



.O. Box 691 Stirling SA

SCALE	DATE	DRAWN	CHECKED
1:500	NOV 2024	DS	TB
PROJECT No	DRAWING No	STATUS	REV
2976	DA02.02	DA	B





108 Mt Barker Road Stirling
South Australia 5152
p: 08 8339 8008
f: 08 8339 2004
P.O. Box 691 Stirling SA 5152
admin@nlelsenarchitects.com.av
NIELSEN ARCHITECTS

SCALE	DATE	DRAWN	CHECKE
1:500	NOV 2024	DS	TB
PROJECT No	DRAWING No	STATUS	REV